

NativeServices.RegistryKeyExists

| Method | RegistryKeyExists | | | | | | | | | | | | |
|----------------------|---|-----------|------------|-------------------|------|---------------------|------|-------------------|------|--------------------|------|------------|-----|
| Module | NativeServices | | | | | | | | | | | | |
| Library | Core | | | | | | | | | | | | |
| Action | Test whether a registry key exists. | | | | | | | | | | | | |
| Parameters | <p>Hive (string): The registry hive which has to match one of the following long or short names, ignoring case:</p> <table border="1"><thead><tr><th>Long Name</th><th>Short Name</th></tr></thead><tbody><tr><td>HKEY_CLASSES_ROOT</td><td>HKCR</td></tr><tr><td>HKEY_CURRENT_CONFIG</td><td>HKCC</td></tr><tr><td>HKEY_CURRENT_USER</td><td>HKCU</td></tr><tr><td>HKEY_LOCAL_MACHINE</td><td>HKLM</td></tr><tr><td>HKEY_USERS</td><td>HKU</td></tr></tbody></table> <p>Subkey (string): The registry key to look for.</p> | Long Name | Short Name | HKEY_CLASSES_ROOT | HKCR | HKEY_CURRENT_CONFIG | HKCC | HKEY_CURRENT_USER | HKCU | HKEY_LOCAL_MACHINE | HKLM | HKEY_USERS | HKU |
| Long Name | Short Name | | | | | | | | | | | | |
| HKEY_CLASSES_ROOT | HKCR | | | | | | | | | | | | |
| HKEY_CURRENT_CONFIG | HKCC | | | | | | | | | | | | |
| HKEY_CURRENT_USER | HKCU | | | | | | | | | | | | |
| HKEY_LOCAL_MACHINE | HKLM | | | | | | | | | | | | |
| HKEY_USERS | HKU | | | | | | | | | | | | |
| Return values | <code>Exists</code> (boolean): Whether the key exists or not. | | | | | | | | | | | | |
| Example | <pre>NativeServices.RegistryKeyExists(Hive:"HKLM", Subkey:"software\\vendor\\settings");</pre> | | | | | | | | | | | | |
| Platforms | <ul style="list-style-type: none">Windows | | | | | | | | | | | | |
| Notes | | | | | | | | | | | | | |