

Nomad.GetCmContentLocations

Method	GetCmContentLocations
Module	Nomad
Library	1E
Action	Find the Configuration Manager locations (on distribution points - DPs) that have the specified content.
Parameters	<code>ContentId</code> (string): The ID of the content to query. <code>Version</code> (int): The version of the content to query.
Return values	For each DP that has the content (maybe none): <code>Hash</code> (string): The hash of the content. (The same value for all rows returned.) <code>Path</code> (string): The URL of the content. <code>SiteLocality</code> (int): The locality of the ConfigMgr site. 0 for unknown locality, 1 for fallback, 2 for remote, or 3 for local. <code>SiteType</code> (int): The type of ConfigMgr site. 0 for unknown, 1 for server, 2 for Azure. <code>IsSmb</code> (bool): <code>false</code> if the Path is an HTTP or HTTPS URL, else <code>true</code> if an SMB share.
Example	What ConfigMgr distribution points, if any, have version 1 of content "Content_7f368e5f-4dbe-4027-ba81-c5463e372a0c"? <pre>Nomad.GetCmContentLocations(ContentId : "Content_7f368e5f-4dbe-4027-ba81-c5463e372a0c", Version : 1);</pre>
Platforms	<ul style="list-style-type: none">Windows
Notes	Requires Nomad v6.3.200 or later. Available from Tachyon v3.2. No data is returned if no DPs have the requested content.