

Interaction.GetActiveResponses

| | |
|----------------------|---|
| Method | GetActiveResponses |
| Module | Interaction |
| Library | Core |
| Action | List all active survey responses. |
| Parameters | (None) |
| Return values | <p>FreeText (string): Free text value input by the user.</p> <p>This value is empty if a free text field was not offered as part of the survey, or if the user never entered a value for this field.</p> <p>Response (string): Text of the survey choice selected by the user.</p> <p>ResponseTime (string): Time when the user responded to the survey, dismissed the survey or it timed out.</p> <p>ResponseType (string): Indicates whether the user responded, dismissed the survey or the survey timed out.</p> <p>ResponseValue (float): The value of the response chosen by the user.</p> <p>The highest ordered choice (first in the table of choices) will have a response value of 1. The lowest ordered choice (last in the table of choices) will have a response value of 0. Those in between will be allocated a fractional value between 1 and 0 relative to their position. For example, if the choices are: (Great, Good, Average, Poor, Terrible) these will be scored (Great=1.0, Good=0.75, Average=0.5, Poor=0.25, Terrible=0)</p> <p>SurveyName (string): Name of the survey.</p> <p>UserName (string): Username of the logon session associated with this survey response.</p> <p>ValidityTime (string): The time when this survey is no longer valid.</p> |
| Example | <pre>@responses = Interaction.GetActiveResponses(); SELECT SurveyName, UserName FROM @responses WHERE ResponseType = "timed out";</pre> |
| Platforms | <ul style="list-style-type: none">Windows |
| Notes | <p>Available from v5.1.</p> <p>For more details on what is considered an active or valid response, see Interaction.ShowSurvey.</p> |