

Scout installer properties

The following table shows the Scout installer properties:

| Name | Default value | Description |
|----------------------|---------------|---|
| AEURL | localhost | The URL for the server where ActiveEfficiency is installed. |
| ALTERNATESMSDBNAME | n/a | Only used when running the Scout in Shopping mode from the Scout scheduler. Set this to the database name for an alternate Configuration Manager. Usually, this is set to the Configuration Manager system that the Shopping central service is pointed at. |
| ALTERNATESMSDBSERVER | n/a | Only used when running the Scout in Shopping mode from the Scout scheduler. Set this to the name for an alternate SQL server hosting the database for Configuration Manager. Normally, this id set to the Configuration Manager system that the Shopping central service is pointed at. |
| APPV | 1 | Determines if the Scout is installed in Configuration Manager mode. <ul style="list-style-type: none">• 0 – Configuration Manager component not installed• 1 – Configuration Manager component instal |
| CONFIGMGRMODE | 1 | Enables Configuration Manager mode. Values are: <ul style="list-style-type: none">• 0 – disables Configuration Manager mode• 1 – enables Configuration Manager mode |
| IQSONARDBNAME | n/a | Name for the iSonar database. |
| IQSONARDBSERVER | n/a | Name of the SQL server where the iSonar database is installed. |
| IQSONARMODE | 0 | Enables the iQSonar mode. Values are: <ul style="list-style-type: none">• 0 – iQSonar mode disabled• 1 – iQSonar mode enabled |
| SERVERMODE | 1 | Installs server component. Values are: <ul style="list-style-type: none">• 0 – server component not installed• 1 – server component installed |
| SMSDBNAME | | Name for the Configuration Manager database. |
| SMSDBSERVER | | Name of SQL server where the Configuration Manager database is installed. |
| SQLWASTEMODE | 0 | Enables SQL waste mode. Values are: <ul style="list-style-type: none">• 0 – disable SQL waste mode• 1 – enable SQL waste mode |